

APPLICATION




If contaminated, use a clay bar to clean. If paint correction is required, do so before application.



Wash and completely dry surfaces to be coated.



Clean the wheel using a 50% IPA (isopropyl alcohol) to water mix in a trigger sprayer. Mist the wheel then wipe down with a microfiber towel.



Wipe on coating by hand using a sponge or coating block. After wiping on wait 30-60 seconds to flash (depending on temp) then buff off with a microfiber towel.



Wait 20 minutes before driving, and 6 hours before getting wet.

WHEEL

WHEEL CERAMIC COATING



PRODUCT OVERVIEW



System X Wheel comprises advanced ceramic technology found in our most durable coatings, blended to become even more corrosion resistant than ever before. This highly chemical-resistant wheel coating works exceptionally well to protect wheels from extremely corrosive and damaging brake dust. System X Wheel easily registers to **CARFAX** with the included QR code sticker to maximize vehicle resale value (US & Canada only).

TECHNICAL DATA

EFFECTIVENESS	Up to 3 years depending on environmental factors
PENCIL HARDNESS	9H
APPLICATION	Wipe on / buff off application or use HVLP gun with 0.8mm tip and buff off by hand
BOTTLE SIZE	20mL, 65mL, 275mL, 4L
SHELF TIME	18 months from shipment date when unopened and stored dry at 13°C (55°F) to 29°C (85°F)
APPEARANCE	Clear / High Gloss
FILM THICKNESS	Up to 0.9 mil
CHEM. RESISTANCE	Outstanding
TEMP. RESISTANCE	> 760°C (1400°F)
SALT SPRAY	(ASTM B117) @ 35°C (95°F), 5% salt concentration, > 400 hrs to first signs of corrosion
ADHESION CROSS-CUT TAPE	(ASTM D3359) 5b (0%, none)
MANDREL BEND	(ASTM D522) 0% @ 180° rotation
IMPACT	(ASTM D2794) 80/80 in/lbs
COVERAGE	180 sq feet (16.7m ²) per 100mL
DRY TIME	40 minutes
CURE TIME	Initial cure in 4 hours, full cure in 3 days
UV PROTECTION	Yes

REGISTERS WITH

